




## Product Bulletin

Product Name

### AMPHOSOL® LB-HP

Chemical Structure



Chemical Description

AMPHOSOL LB-HP is a mild amphoteric surfactant derived from naturally derived coconut oil. This characteristic gives the product enhanced foaming properties compared to broad homolog distribution. AMPHOSOL LB-HP meets the U.S. EPA Safer Choice Program's surfactant screen and is listed on Cleangredients. It is used in personal care, home care and industrial products.

CAS Registry No.

4292-10-8 and 59272-84-3

INCI Name

Lauramidopropyl Betaine

Applications

Functional Properties

- Primary or secondary surfactant
- Foam booster
- Viscosity builder
- Static Control agent
- Compatible with anionics, nonionics and cationics

End Product Uses

- |                     |                                    |
|---------------------|------------------------------------|
| • Bubble Baths      | • Hand Soaps                       |
| • Hair Conditioners | • Shower Gels                      |
| • Shampoos          | • Pet Shampoos                     |
| • Baby Products     | • Light Duty Liquid Dish Detergent |

Typical Properties

Appearance at 25°C .....	Clear liquid
Solids, %.....	36.5
pH, as is.....	12.0
Free Amidoamine, %.....	1.0 max.
Sodium Chloride, %.....	5.3
Color, APHA .....	100 max.
Actives, %.....	30
Flash Point, PMCC, °C (°F).....	>94 (>201)
Viscosity at 25°C, cps.....	13
RVOC, U.S. EPA, %.....	0
Preservative.....	Not required

Environmental Effects

Product is readily biodegradable. Additional information is available upon request.



## Health Effects

AMPHOSOL LB-HP is practically nontoxic orally ( $LD_{50} > 5000$  mg/kg) and is expected to be moderately irritating to eyes and minimally to non-irritating to skin at 10% active when tested at a neutral pH.

## Storage & Handling

Normal safety precautions (e.g., gloves and safety goggles) should be employed when handling AMPHOSOL LB-HP. Contact with eyes, nose or prolonged contact with skin should be avoided. Wash thoroughly after handling AMPHOSOL LB-HP. See SDS for more information.

Non-Bulk Storage Recommendations: AMPHOSOL LB-HP should be stored in closed containers and kept in a cool, dry place away from incompatible materials (see Section 10 of the SDS) at temperatures between 40°F (4°C) and 110°F (43.3°C). If material is frozen it should be heated gently and stirred to ensure it is homogeneous prior to use.

Standard Packaging: AMPHOSOL LB-HP is available in bulk and drums.

## Workplace Exposure

Occupational exposure can occur primarily through skin contact or via inhalation of vapors and mists. Engineering controls, personal protective equipment, and other workplace safety practices should be used to control these exposures. See SDS for more information.

## Clearances

The international inventories (country clearances) of AMPHOSOL LB-HP can be found in Section 15 of the Safety Data Sheet (SDS). It is the responsibility of the formulator to review the chemical control regulations for each country where the end-product is intended to be sold or used. If you have any further questions regarding inventories, please contact North America Technical Service at [techserv@stepan.com](mailto:techserv@stepan.com).

AMPHOSOL LB-HP meets the U.S. EPA Safe Choice Program's surfactant screen and is listed on [www.cleangredients.org](http://www.cleangredients.org) (an on-line database for green formulators). For further information, visit [www.cleangredients.org](http://www.cleangredients.org). Additional Stepan ingredient listing can be found at [www.stepan.com](http://www.stepan.com).

## Product Stewardship

This product bulletin has been written in accordance with ACC's Product Stewardship guidelines.

## Additional Safety Information

A Safety Data Sheet (SDS) is available upon request.



The information contained herein is based on the manufacturer's own study and the works of others and is subject to change without prior notice. The information is not intended to be all-inclusive, including as to the manner and conditions of use, handling, storage or disposal or other factors that may involve additional legal, environmental, safety or performance considerations. Nothing contained herein grants or extends a license, express or implied, in connection with any patents issued or pending of the manufacturer or others, or shall be construed as a recommendation to infringe any patents or to violate any applicable laws. STEPAN COMPANY MAKES NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR USE, EXPRESS OR IMPLIED, AND NO OTHER WARRANTY OR GUARANTY, EXPRESS OR IMPLIED, IS MADE, INCLUDING AS TO INFORMATION REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY, ACCURACY, COMPLETENESS OR ADEQUACY. Stepan Company (and its employees, subsidiaries and affiliates) shall not be liable (regardless of fault) to the vendee, its employees, or any other party for any direct, indirect, special or consequential damages arising out of or in connection with the information provided herein, including in respect of its accuracy, completeness, adequacy, furnishing, or use, or reliance upon such information. The vendee assumes and releases Stepan Company (and its employees, subsidiaries and affiliates) from all liability, whether in tort, contract or otherwise to the fullest extent possible under the relevant law.

**Stepan**   
**Corporate Headquarters**  
**Northfield, Illinois 60093, U.S.A.**  
**Phone: 847-446-7500**  
**Fax: 874-501-2100**  
**Website: [www.stepan.com](http://www.stepan.com)**

For Technical Service Call:  
Stepan North America **+1-800-745-7837**  
Stepan Mexico **+55-11-5089-2208**  
Stepan Quimica **+55-11-5089-2200**  
Stepan Colombia **+571-636-2808**  
Stepan Europe **+33-476-505-160**  
Stepan Asia **+656-879-9855**  
Stepan Philippines **+656-879-9855**

For Customer Service Call:  
Stepan North America **+1-800-457-7673**  
Stepan Mexico **+52-555-533-1967**  
Stepan Quimica **+55-11-5089-2200**  
Stepan Colombia **+57-6-8993125**  
Stepan UK **+44-161-338-5511**  
Stepan France **+33-476-50-51-00**  
Stepan Philippines **+63-2-842-7951**