Stepan 5. Formulation		
Name ULTRA FABRIC SOFTENER DISPERSION USING 15% SOLIDS		
No.	STEPANTEX® VT-90 1130	
Description	This 15%-solids fabric softener is for use in the rinse cycle of the wash load. It is non-yellowing and provides excellent softening and static control while maintaining the rewet properties of the fabric.	
Formulation	INGREDIENTS:	<u>% by Weight</u> Functionality
	Deionized Water STEPANTEX® VT-90 Calcium Chloride (20% by wt. solution) Ucarcide 250M Dye, Fragrance, Preservative	82.53 Carrier 16.67 Softener 0.75 Viscosity Adjuster q.s.* Preservative q.s. Additives
	Total	100.00
Procedure	 Charge Deionized Water at 55°C/131°F or heat it up to this temperature in the vessel. Dye can be added at this time. While mixing, slowly add STEPANTEX® VT-90 (which has been previously heated to a temperature of 50°C/122°F) to the water and agitate for 10 minutes. The esterquat will disperse into a thick cream-like consistency. Add Calcium Chloride solution to reduce viscosity and stabilize the system. Continue mixing for another 20 minutes. When the temperature has reached 35°C/95°F, charge Preservative and any other ingredients (e.g. Fragrance, optical brightener, etc.). * Use amount recommended by supplier. 	
Physical Properties	Appearance at 25°C/77°F pH, as is Viscosity at 25°C/77°F, cPs (Brookfield DV-II+ Pro) Solids, % Density, Lb/gal	Opaque liquid 3.0 Water-like 15.0 8.34
Storage/ Stability	4 weeks at 5°C/41°F 4 weeks at 40°C/104°F 4 weeks at 50°C/122°F	Stable Stable Stable
Instructions for Use	Use 1 oz. in rinse cycle for a regular wash load (4–6 lbs).	
External Comment	For a more viscous product, the calcium chloride amount can be reduced. Final viscosity may vary, depending on the processing temperature, mixing rate, and time. Fragrance and other ingredients may also affect this parameter. Sodium chloride can also be used to adjust viscosity. Monitoring viscosity of the final fabric softener product at the storage temperature requirements is recommended.; Marketing Notes: STEPANATEX® VT-90 is an approved ingredient on www.cleangredients.org. For further information, visit our website or www.cleangredients.org. BCI	

= 81. Total BCI (Biorenewable Carbon Index) was calculated only for the Stepan surfactants used in this formulation.

Registered Trademarks of Stepan Company

For Additional Assistance For applications or product handling assistance, call our Technical Service Department at 1-800-745-7837 (U.S.) or 011-334-76-505-100 (Europe).

For ordering assistance, call our Account Service Department at 1-800-457-7673.

The information contained herein is based on the manufacturer's own study and the works of others and is subject to change without prior notice. The information is not intended to be all-inclusive, including as to the manner and conditions of use, handling, storage or disposal or other factors that may involve additional legal, environmental, safety or performance considerations. Nothing contained herein grants or extends a license, express or implied, in connection with any patents issued or pending of the manufacturer or others, or shall be construed as a recommendation to infringe any patents. STEPAN COMPANY MAKES NO PRODUCT WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR USE, EXPRESS OR IMPLIED, AND NO OTHER WARRANTY OR GUARANTY, EXPRESS OR IMPLIED, IS MADE, INCLUDING AS TO INFORMATION REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY, ACCURACY, COMPLETENESS, OR ADEQUACY. Stepan Company (and its employees, subsidiaries and affiliates) shall not be liable (regardless of fault) to the vendee, its employees, or any other party for any direct, indirect, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy, furnishing, use, or reliance upon information provided herein. The vendee assumes and releases Stepan Company (and its employees, subsidiaries and affiliates) from all liability, whether in tort, contract or otherwise to the fullest extent possible under the relevant law.



STEPANTEX®

Stepan Company Northfield, Illinois 60093 Telephone (847) 446-7500

Revision Date: Publication Date: 08/18/2010 © 2015, Stepan Company. All rights reserved.