

Name INDUSTRIAL TRIPLE-FOAM BASE FOR CAR WASH

No. 1198

Description | A concentrated formulation that when diluted, provides a large amount of colored foam for use

as a car wash.

Formulation INGREDIENTS: % by Weight Functionality

Deionized Water q.s. to 100.0 Diluent

BIO-TERGE® AS-40K 60.0 Primary Surfactant AMMONYX® LMDO 3.3 Secondary Surfactant

STEPANATE® SXS

Dowanol DPnB (Dow) Dipropylene Glycol n-Butyl Ether

Dye
Fragrance
Fragrance
Preservative

3.0 Hydrotrope
3.0 Solvent
3.0 Additive
3.0 Additive
q.s. Additive

Total 100.0

Procedure Mix ingredients in order shown until homogenous.

Physical Appearance at 25°C Clear liquid

Properties pH, as is 8.5 Viscosity at 25°C, cps 8.5

Viscosity at 25°C, cps < 50 Solids, % 30 VOC (calculated) at 1:200 dilution level, % 0

Storage/ 4 weeks at 50°C Stable
Stability 4 weeks at 25°C Stable

4 weeks at 25°C Stable
4 weeks at 4°C Stable

Freeze/thaw, 3 Cycles Stable

Instructions for Use

This formulation is to be diluted to 1:200 and applied with the proper car-wash equipment.

External Comment

Marketing Notes: When used at Stepan's recommended dilution level of 1:200, this formulation is VOC-compliant with U.S. Federal and California Air Resource Board (CARB) Consumer Products regulation for non-aerosol, motor vehicle wash (0.2% VOC limit as of December 31, 2012). Dowanol DPnB is a low-vapor pressure VOC (LVP-VOC) and is exempt from the VOC calculation. BIO-TERGE® AS-40K, AMMONYX® LMDO and STEPANATE® SXS are approved ingredients on www.cleangredients.org. For further information, visit our website or www.cleangredients.org. Label and/or trademark usage of the final product is the sole responsibility of the finished product manufacturer. This product does not contain Nonylphenol Ethoxylates (NPEs). Dye and Fragrance must be at 3% by weight so that when diluted, foam will remain colored and fragrance will remain noticeable. Typical dyes used are red, blue and gold.

Registered Trademarks of Stepan

BIO-TERGE® AMMONYX®

## **STEPANATE®**

Company

For Additional Assistance For applications or product handling assistance, call our Technical Service Department at 1-800-745-7837 (U.S.) or 011-334-76-505-100 (Europe).

For ordering assistance, call our Account Service Department at 1-800-457-7673.

The information contained herein is based on the manufacturer's own study and the works of others and is subject to change without prior notice. The information is not intended to be all-inclusive, including as to the manner and conditions of use, handling, storage or disposal or other factors that may involve additional legal, environmental, safety or performance considerations. Nothing contained herein grants or extends a license, express or implied, in connection with any patents issued or pending of the manufacturer or others, or shall be construed as a recommendation to infringe any patents or to violate any applicable laws. STEPAN COMPANY MAKES NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR USE, AND NO WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE, INCLUDING REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY, ACCURACY, COMPLETENESS, ADEQUACY OR OTHERWISE. Stepan Company (and its employees, subsidiaries and affiliates) shall not be liable (regardless of fault) to the vendee, its employees, or any other party in respect of this information, including in respect of its accuracy, completeness, adequacy, furnishing, use, or reliance upon, and the vendee assumes and releases Stepan Company (and its employees, subsidiaries and affiliates) from all liability, whether in tort, contract or otherwise.



Stepan Company Northfield, Illinois 60093 Telephone (847) 446-7500

Revision Date: Publication Date: 05/22/2013 © 2016, Stepan Company. All rights reserved.